

# ⊕ Accessories/other products





**Wall collar MK**

Hydrostatic sealing of steel, cast iron, copper, plastic, glass fibre reinforced concrete, concrete and vitrified clay pipes through walls, ceilings, floors, manhole entries, swimming pools and groundwater basins. The UGA wall collar is the right solution wherever a wall sleeve or core drilling can no longer be retrofitted. Wall collar MK for pipe outer diameter 32–1450 mm. Supplied with corresponding metal clamping straps.

- Leak-tight against pressing water
- Radon-tight
- Numerous sizes



4 bar

**Product name:**  
MK(A)



**Cable funnel insert KT**

The KT cable funnel allows cables to be inserted quickly, reliably and gently into conduit ducts. The rounded edges prevent damage to the cable insulation. The KT cable funnel inserts are available in three different sizes with three different sleeve variants for pipes with outer diameters of 110 mm, 125 mm and 160 mm. Several elements can be stacked on top of and next to each other to form a package. Unused cable funnel inserts can be easily sealed with a sealing insert.

- Protection of the cable insulation
- Bundle possible
- No additional formwork aids necessary

**Product name:**  
KT(A)/(L) (adhesive sleeve)  
KT(A)-SM-EFL/(A)/(L) (pipe fitting, single lip seal)  
KT(A)-SM-MFL/(A)/(L) (pipe fitting, multiple lip seal)



**EPDM sleeves**

High-quality EPDM sleeves for connecting or joining smooth-walled pipes, corrugated pipes and cable protection systems. Available in various sizes in a clamping range of 40–250 mm.

- Simple gas-tight and watertight connection and joining possible
- High-quality EPDM sleeves with a defined clamping range for various applications
- Use of high-quality tensioning straps made of V4A stainless steel



0.5 bar

**Product name:**  
MA (A1–A2)/(A3–A4)

Legend: Gas-tight and watertight up to ... bar











**Want to know more?**














You can find further information in the product data sheets and installation instructions in the download area of our website. Scan this QR code to get there.



Product name	Product description	Areas of application
<b>3-finger (partitioned) shrink sleeves AK</b>	Hot-shrink technology for sealing three cables in one system cover socket, available in different variants. <b>AK35/3F/2-12</b> for system cover <b>BKD150-D-8/35/25</b> ; suitable for cables with an outer diameter of 2–11 mm <b>AK50/3F/5-22</b> for system covers <b>BKD150-D-8/35/25</b> and <b>BKD150-D-7/38</b> ; suitable for cables with an outer diameter of 5–21 mm <b>AK75/3F/8-29</b> for system cover <b>BKD150-D-3/59</b> ; suitable for cables with an outer diameter of 8–28 mm	  
<b>4-finger (partitioned) shrink sleeves AK</b>	Hot-shrink technology for sealing four cables in one system cover socket, available in different variants. <b>AK35/4F/2-13</b> for system cover <b>BKD150-D-8/35/25</b> ; suitable for cables with an outer diameter of 2–12 mm <b>AK50/4F/5-20</b> for system cover <b>BKD150-D-8/35/25</b> and <b>BKD150-D-7/38</b> , suitable for cables with an outer diameter of 5–19 mm <b>AK75/4F/8-29</b> for system cover <b>BKD150-D-3/59</b> , suitable for cables with an outer diameter of 8–28 mm	  
<b>Spacer ASH for cable protection systems</b>	Spacer <b>ASH 2 x 3</b> for <b>KSS150/110/125</b> for positioning and fixing a maximum of 6 KSS hoses, 3 next to each other and 2 above each other. For the following variants: <b>ASH170/2x3: KSS150</b> <b>ASH140/2x3: KSS125</b> <b>ASH125/2x3: KSS110</b>	
<b>Spacer ASH for wall insert variants</b>	Spacer for the BKD 150 wall insert variants, increases the centre distance by 40 mm to a total of 250 mm.	

Legend: Cable entries Sealing inserts Wall sleeves Cable protection systems House lead-ins Roof entries Fire protection

Product name	Product description	Areas of application
<b>Aquagard primer</b>	<p>Primer for sealing core drillings. The primer penetrates deep into the capillaries and air bubbles in the concrete and seals them permanently watertight. This prevents water from travelling around the sealing insert.</p> <p>The primer is applied with a brush or roller.</p> <p>1 litre for 4.0 m<sup>2</sup> (type 1710) 1/3 litre for 1.5 m<sup>2</sup> (type 1711)</p>	
<b>Aquagard special varnish</b>	<p>Special solution for sealing core drillings. The Aquagard special solution seals the surface of the core drill hole and at the same time protects any cut reinforcement steel from corrosion. The special sealer is applied with either a brush or a roller.</p> <p>1 litre for 3.5 m<sup>2</sup> (type 1715) 1/3 litre for 1.0 m<sup>2</sup> (type 1716)</p>	
<b>CV connector 110</b>	CV connector for sealing exposed DN 110 corrugated pipe ends with sealing insert (not included).	
<b>CV connector 160</b>	CV connector for sealing exposed DN 160 corrugated pipe ends with sealing insert (not included).	
<b>Disassembly set M8</b>	Disassembly aid for easy and safe disassembly of sealing inserts with M8 threaded bolts. Usable length up to 100 mm, consisting of 2 pieces in a set.	 
<b>Disassembly set M6</b>	Disassembly aid for easy and safe disassembly of sealing inserts with M6 threaded bolts. Usable length up to 100 mm, consisting of 2 pieces in a set.	 
<b>Torque spanner assembly set GPD/RRD</b>	Metal case with the following contents: torque spanner 4–20 Nm, 1/4 inch; extension 1/4 inch 150 mm; socket spanner bit SW 10 (M6) long version; socket spanner bit SW 13 (M8) long version	 
<b>Hinged face spanner GSS</b>	For mounting all system covers and KSS systems; with adjustable handle.	

Product name	Product description	Areas of application
<b>Lubricant</b>	Bag of neutral soap-based lubricant for sealing inserts; fill quantity 10 grams.	 
<b>Rubber stopper</b>	EPDM rubber plugs for closing openings in sealing inserts. Available in various rubber thicknesses and diameters.	 
<b>HandyMax cartridge gun (2KNE, ZZ330)</b>	HandyMax 2K cartridge gun for 2K coaxial cartridges (5:1), e.g. 380 ml, suitable for ZZ 330 fire protection foam (2K NE).	
<b>Cable cleaner 1 litre</b>	For cleaning all types of cables, even with stubborn dirt. Odourless and evaporates without leaving any residue. Fill quantity 1,000 ml. Density at 20 °C: 0.764 g/cm <sup>3</sup> . Flash point: > 61 °C. Evaporation rate: 60. Labelling: Xn.	  
<b>Cold-shrink sleeves</b>	For quick and easy installation without tools, in all weathers. Gas-tight and watertight up to 2 bar. Available for all system covers.	  
<b>Metal tensioning strap</b>	Metal tensioning strap for fastening fire protection fabrics and bandages in compliance with approvals, 100 m long x 15 mm wide.	
<b>Mixer attachment 2K</b>	Mixer attachment 2K for 2K coaxial cartridges, suitable for ZZ 330 fire protection foam (2K NE).	

Legend:

						
Cable entries	Sealing inserts	Wall sleeves	Cable protection systems	House lead-ins	Roof entries	Fire protection

Product name	Product description	Areas of application
Mounting set FU-FZ	UGA mounting set for split fibre cement wall sleeves. Installation set available for all wall thicknesses up to an internal diameter of 450 mm.	
OTTOPUR Cleaner for fire protection foams	OTTOPUR Cleaner for fresh PUR foams, 500 ml. OTTOPUR Cleaner is suitable for easy removal of fresh, uncured PUR foams, e.g. for ZZ 330 fire protection foam (2K NE).	
Power Max cartridge gun	Rechargeable PowerMax cartridge gun 2K for 2K coaxial cartridges (5:1), e.g. 380 ml, incl. rechargeable battery, suitable for ZZ 330 fire protection foam (2K NE).	
Sikadur®-31-CF	Solvent-free thixotropic two-component adhesive and repair mortar based on epoxy resin. Available in 1.2 kg.	
Sikaflex®-11 FC Purform®	Cartridge containing 300 ml of elastic sealant for optimising wall surfaces and for bonding our components to all types of wall.	 
Tensioning strap	Tensioning strap available in various sizes.	
Step flap	UGA step flap for sealing inserts to protect against slipping. Various sizes available in a set of 2 pieces.	
Tangit M3000	Two-component polyurethane-based resin. Self-filling compound that expands up to five times its volume. Ideal for watertight and gas-tight sealing of smaller wall and floor penetrations.	
Hot-shrink sleeves	UGA hot-shrink sleeves for cables and pipes in various sizes.	  

Product name	Product description	Areas of application
Hot-shrink sleeve set	UGA hot-shrink sleeve set for system covers of cable entries. Two hot-shrink sleeves for DN 35 mm and two hot-shrink sleeves for DN 25 mm.	  
Locking clips	Locking clips for approval-compliant fastening of metal tensioning straps when using fire protection fabrics and bandages, 1,000 pieces.	
Sealing plug	For sealing unused system cover spigots. Can be quickly removed again when refitting. Version available for all system covers.	  
Interchangeable insert	UGA interchangeable insert made of EPDM rubber for sealing inserts with interchangeable insert. Available with rubber thickness 60 mm as: WE50, WE65, WE85, WE110, WE125. The interchangeable inserts can be supplied blind or with customised assignment.	 
WEICON Flex 310 M® Super Adhesion	Cartridge containing 290 ml of elastic adhesive and sealing compound based on MS polymer. For use on black troughs (thick bitumen coating) for tested products with subsequent flange.	 
Sealing plugs	EPDM rubber Sealing plugs (rubber thickness 3 mm) available for all flange constructions.	 
Multilayer insert	UGA multilayer insert made of EPDM rubber for sealing inserts and BKD150 system inserts. Available with a rubber thickness of 40 mm as: ZS4-20, ZS4-25, ZS4-32, ZS22-54.	 

Legend:

Cable entries	Sealing inserts	Wall sleeves	Cable protection systems	House lead-ins	Roof entries	Fire protection



## Get in touch with us!

**E-MAIL** [info@uga.eu](mailto:info@uga.eu)

**HOTLINE** +49 7324 9696-33

## Contact person

Scan this QR code to find the right contact person for your in-house or field service:

