

System insert with interchangeable insert

BKD150-E-WE



Application range

- For sealing packs and mounting flanges BKD150 as well as compatible systems

Material specifications

- Metal press plates (V2A or V4A)
- Rubber blank (EPDM)
- Threaded bolt and nuts (V2A or V4A)
- Interchangeable insert (EPDM)

Technical information


- Gas- and watertight up to 2 bar
- Radon-tight
- Metal press plates 5 mm
- Welded threaded bolts
- For cables and pipes $\varnothing a$ 4 – 76 mm
- Interchangeable insert with individual configuration
- Rubber width: 34 mm (system insert)
- Rubber width: 64 mm (interchangeable insert)
- Fixation by bayonet lock
- Reinforced, circumferential rubber edge as depth stop
- Split insert for installation after cable laying
- Integrated mounting holes in the press plates for hinged face spanner (accessories)

Test reports

- LRQA up to 2 bar


Front view system insert

BKD150-E-WE



Side view system insert

BKD150-E-WE



System insert with interchangeable insert

BKD150-E-WE



Maximum occupancy table: system insert with interchangeable insert

Z = Number of cables / lines	D = Diameter of cables / lines
0	Blind plug possible
1	up to 110 mm
3	up to 42 mm
5	up to 34 mm
7	up to 29 mm
9	up to 24 mm

Other configurations and combinations, also with different diameters, possible